

Oscillating Spindle/Belt Sander

OSS-2

4.3A

4X24" sanding belt speed is 1565 FPM.

Oscillating & Rotating action: For speed & precision finishing work.

Dust port: assists in dust extraction to create a cleaner , safer work environment.

Sanding drum
1/2 " , 3/4 " , 1 " , 1-1/2 " ,
2 "(inner)
3/5 " , 4/5 " , 1 " , 1-3/5 " ,
2 "(outer)

Onboard storage

Powerful 4.3A motor: ideal for sanding contours, arcs, curves & irregular shapes.

Tilting cast alu table top:
Adjust 0-45 degrees to support angles & chamfering.



Onboard storage



Oscillating & Rotating action



Large working table



- Powerful 4.3A motor: ideal for sanding contours, arcs, curves & irregular shapes
- 4X24" sanding belt speed is 1565 FPM
- Oscillating & Rotating action: For speed & precision finishing work
- Large working table of 15.7x16" for your convenience
- Miter gauge(0-60 degree sanding)
- Variable-speed control
- Tilting cast aluminum table top : Adjust 0-45 degrees to support angles & chamfering
- Dust port: assists in dust extraction to create a cleaner , safer work environment
- Sanding drum 1/2 " , 3/4 " , 1 " , 1-1/2 " , 2 "(inner) ; 3/5 " , 4/5 " , 1 " , 1-3/5 " , 2 "(outer)



Oscillating Spindle/Belt Sander

Current 电流	Motor Speed 马达速度	Table Size 工作台尺寸	Oscillations 振荡	Oscillations Stroke 振荡行程	Max Sanding Depth 最大磨削深度	Sanding Dia 主轴直径	Spindle Height 主轴高度	Dust Port Dia. 排尘口直径	Package Size 包装尺寸	N.W./G.W. 净重/毛重
4.3A	2000RPM	15.7*16 inch	58opm	3/5 inch	3-1/2 inch	1/2 inch	4-1/2 inch	1-2/5"(inner) 1-1/2"(outer)	21*18*19 inch	27.5/31 lb